

... from development to
implementation



Production of materials testing equipment and automation

Electromechanical testing actuators LABTEST ASD





Electromechanic testing actuators LABTEST ASD for static and dynamic applications.

Technical description

Linear ASD actuators have been developed as actuators generating a pushing or pulling force relative to the reference point. The principle of the actuator is based on the conversion of rotational motion to linear. The desired axial force (static and dynamic) and the desired speed can be achieved by selecting the actuator and the actuator body (see the table for more information). Other usable features and features can be obtained:

Variable speed and force, force detection, force limitation, positionability, high accuracy, easy installation and maintenance, low maintenance costs and long life, etc.

Field of use

- Alternative substitution of hydraulic and pneumatic cylinders
- One or multiple testing of materials, assemblies and components
- Testing under atypical conditions (temperature chambers, etc.)
- Cyclical tests with large strokes
- Testing in clean and sterile facilities

Characteristic features

- Speed up to 500 mm/s
- Control via 5 kHz EDC series electronics
- Control via PC and T&M software or RMC remote control
- Easy installation of LC LABORTECH series load cells
- Multi-axial product testing on one PC



... from development to implementation

Chart of electromechanic actuator series ASD

Technical data	Units	ASD1.0	ASD1.1	ASD2.0	ASD2.1	ASD5.0	ASD5.1	ASD10.0	ASD10.1	ASD20.0	ASD30.0	ASD50.0	ASD100.0	
	kN	1	1	2	2	5	5	10	10	20	30	50	100	
Maximal testing speed	mm/sec	125	500	125	250	85	500	55	250	125	100	50	41,6	
Maximal testing speed	m/min													
Machine drive resolution	µm	±2,5	±6	±2,5	±6	±2,5	±8	±8	±8	±8	±8	±8	±0,014	
Position repeatability	kg													
Maximal standard stroke		200	180	200	200	200	200	200	200	200	200	200	200	
Maximal alternative stroke		400	380	400	400	400	400	400	400	400	400	400	400	
Weight ¹	kg	22	26	22	26	26	72	65	72	72	72	113	420	
Length (A)	mm	547	547	547	547	547	669	669	669	669	669	682	950	
Width (B)	mm	120	120	120	120	120	180	180	180	180	180	200	296	
Height (C)	mm	270	270	270	270	270	385	385	385	385	385	430	510	
Length incl. load cells (D)	mm													
Environmental conditions														
Ambient temperature	°C													from 10 to 35
Storage temperature	°C													from -35 to 55
Humidity	%													< 90
Noise	dB													< 65
Electrical connection														
Powering	V	230 1Ph/N/PE	230 1Ph/N/PE	230 1Ph/N/PE	230 1Ph/N/PE	230 1Ph/N/PE	400 3Ph/N/PE	230 1Ph/N/PE	400 3Ph/N/PE	400 3Ph/N/PE	400 3Ph/N/PE	400 3Ph/N/PE	400 3Ph/N/PE	
Fuse	A													
Machine input (without accessories)	kVA	2,2	2,2	2,2	2,2	2,2	5,0	2,2	5,0	5,0	5,0	5,0	5,0	5,0

... from development to implementation

Labor Tech®

Production of materials testing equipment and automation

Electromechanical testing actuators
LABTEST ASD

LABORTECH in the world



Contact:

LABORTECH s.r.o.

Rolnická 130a, 747 05 Opava, Czech Republic
Phone: +420 553 731 956, +420 553 668 648
E-mail: info@labortech.cz
Web: www.labortech.cz
GPS: 49°57'05.1"N
17°54'04.4"E

LABORTECH TRADING s.r.o.

Areál VVÚD Praha, Na Florenci 1686/9, 111 71 PRAHA 1, Czech Republic
Phone: +420 731 656 723, +420 724 020 052
E-mail: trading@labortech.cz
Web: www.labortech.eu

Follow us on our social media networks and Youtube channel:

[Youtube](#), [Linkedin](#), [Facebook](#)



Production of materials testing equipment and automation

LABORTECH in the world

... from development to implementation